



MODEL NUMBER	HEAT INPUT MJ/H	HEAT OUTPUT KW		AIR FLOW (l/s AT 75Pa ESP)		WEIGHT KG	POWER SOURCE		CURRENT AMPS TOTAL/FLA/LRC	NOM. COOLING KW (Sensible / Total)		A	B	C	D	E
		HIGH	LOW	HIGH	LOW		VOLTS/PH/Hz	CONTROL VOLTAGE VAC		KW (Sensible / Total)						
EXS408	90	18.8	600	500	150	240/1/50	24	15/12/45	4.8/6.5	1690	500	1115	200	350		
EXS409	90	18.8	700	540	170	240/1/50	24	22/19/40	7.5/10.0	1690	500	1115	200	350		
EXS408	120	25.0	870	700	200	240/1/50	24	26/19.6/42	9.0/12.0	1690	760	1270	200	400		
EXS409	120	25.0	870	700	208	240/1/50	24	28/20.4/45	10.8/14.4	1690	760	1270	200	400		
EXS409	150	32.0	1000	740	220	240/1/50	24	28/20.4/45	10.8/14.4	1690	760	1270	200	400		
EXS420T	120	25.0	870	700	208	415/3/50	24	12/PH/8.6/56	12.6/15.5	1690	760	1270	200	400		
EXS420T	150	32.0	1000	740	220	415/3/50	24	12/PH/10/60	14.5/18.0	1690	760	1270	200	400		